

Talos

CROSSTECH Zip up Firefighter boots



Technology

DDR



injected Dual Density Rubber Sole



Features

Standard	EN ISO 15090:2012 EN ISO 20345:2011 AS/NZS 4821:2014
Category	F2A HI3 CI AN SRC. S3 CR WR HI CI HRO SRC.
Code	NFSR1116
Product type	Fire boot
Colour	Black
Size range	UK sizes 2 - 15 continental 36 - 50
Weight	1.36kg
Upper	Flame Retardant, Hydrophobic, water resistant and breathable full grain cow hide leather (2.5 – 2.7mm)
Inner lining	CROSSTECH® footwear laminate, durable waterproof and breathable moisture barrier, protecting against liquid penetration, blood and body fluids.

Safety features

Stainless Steel Toe Cap, resistant to 200J.
Protective midsole
Cut resistant strip 35mm above nip line.
Ankle impact protector.

Additional features

Quick release front YKK Zip.
Flex areas for ease of bending and kneeling.
Reflective panels.
Ridged Rubber Cap for extra strength and durability.
Lock D ring.

Soling technology

Lightweight Injected flame retardant Dual Density Rubber/Rubber, flexible soling system with antistatic properties, shock absorption, heat resistance to 300°C and SRC rated slip resistance.

Insole / Footbed technology

Open Cell PU dual density PU insole. Removable and washable.



Steel Toe



Penetration Resistance



Cut Resistance



F2A



Shock Absorption



Dual Density Direct Injection Sole System



Breathable



Anti-static



Fuel Oil Resistant



Heat Resistant Outsole



Non-Wicking Lace & Thread



Waterproof



Fire Retardant Lace & Thread