

# Talos - Fire Boots



## Safety Standard:

EN ISO 15090:2012- F2A HI3 P CI AN SRC  
EN ISO 20345: 2011- S3 FO CI HI CR HRO WR SRC AN  
EN ISO 20345: 2022+A1:2024-  
S7L FO CI HI CR HRO WR SR SC LG AN



## Features:

**Code:** NFSR1116

**Type:** Firefighter Boot

**Colour:** Black

**UK sizes:** 2 - 15 EU 35- 50

**Upper material:** Flame retardant, Hydrophobic, Breathable Full Grain Cow Hide Leather (2.5 – 2.7mm)

**Inner lining:** CROSSTECH® durable, waterproof, breathable moisture barrier, protecting against liquid penetration, blood and body fluids.

## Safety Features:

Metallic Toe Cap, resistant to 200J

Composite Protective Midsole to 1100N

## Additional features

Injected Ridged Rubber Cap

Ankle Protection

Reflective Panels

Front Zip and Lace Fitting

## Soling technology

Lightweight Injected Dual Density

Rubber/Rubber, flexible soling

system with antistatic properties, shock absorption, heat resistance to 300°C and SR rated slip resistance.


## Insole technology

Moisture wicking, breathable and washable

Open Cell PU Footbed.



## Technology:



Flex Zone



Ankle Protection



Shock Absorption



Dual Density Direct Injection Sole System



Steel Toe



Rigid Rubber Cap



Fuel Oil Resistant



Fire Retardant Lace & Thread



Waterproof



Penetration Resistance (Textile)



F2A



Anti-static

[www.goliath.co.uk](http://www.goliath.co.uk)

